

Philips LED Bulb

5.5W (40W)

Warm white Non-dimmable

8718696577097



Light that's easy on your eyes

Comfortable light from the world leader in lighting

Poor quality light could cause eye strain. It's more important than ever to properly light your home. Philips LED lamps fulfill stringent test criteria to ensure they meet our Eyecomfort requirements†

Choose for high quality light

• True incandescent-like warm white light

Light beyond illumination

• A simple LED for everyday use

Choose a simple replacement for your old bulbs

• Instant light when switched on

Choose for a sustainable solution

- · Long life bulbs Lasts up to 15 years
- Better for your wallet and your planet

Comfortable LED light that is easy on your eyes

- · Designed for the comfort of your eyes
- · No visible flicker



Highlights

Incandescent-like warm white



This bulb has a color temperature of 2700K, providing you with a warm, tranquil atmosphere, perfect for relaxing. This 2700K light is ideal for home lighting design

A simple LED for everyday use



The Philips everyday LED is the perfect bulb for your basic lighting needs. It provides the beautiful light and dependable performance you expect from LED at an affordable price.

Instant On



No need to wait: Philips LED light bulbs provide their full level of brightness

immediately when they are switched on. Just by flipping the switch, your room is at full brightness. There is no slow starting or waiting.

15,000-hour rated average life



With a lifetime of up to 15,000 hours, you can reduce the hassle of frequently replacing your light bulbs, and enjoy a perfect lighting solution for over 15 years.

Saves up to 80% energy



LED technology saves up to 80% energy compared to your standard bulb. It therefore pays for itself and saves you money year after year. It also helps protect the environment.

Gentle LEDs, easy on the eyes



It's easy to see how harsh lighting can strain the eyes. Too bright, and you get the glare. Too soft and you experience flicker. Now you can gently light up your world with LEDs designed to go easy on the eyes, and create the perfect ambience for your home.

No visible flicker

When your light flickers in quick succession it could be hard on the eyes, cause headaches, and even set off an attack for those with photosensitive epilepsy. It's both unpleasant and unnecessary. LEDs can flicker because of their rapid response to the driver current. However, because Philips LEDs are designed so that variations in your driver current's output are minimized, they eliminate the factors that cause flicker. So, you won't see it, not even a hint.

Specifications

Bulb characteristics

- · Shape: Bulb
- Cap/fitting: E27
- Dimmable: No
- Voltage: 220 240 V
- Wattage: 5.5 W
- Wattage equivalent: 40 W

Power consumption

- Energy efficiency label: A+
- Power consumption per 1000h: 6 kW h

Light characteristics

- Light output: 470 lumen
- Beam angle: 200 degree
 Color: Warm White
- Color temperature: 2700 K
- Color rendering index (CRI): 80
- Starting time: < 0.5 s
- Warm-up time to 60% light: Instant full light
- Application: Soft light
- EyeComfort: Eye Comfort

Durability

- Lifetime of lamp: 15000 hour(s)
- Number of switch cycles: 50000
- Lumen maintenance factor: 0.7
- Average life (at 2.7 hrs/day): 15 year(s)

Bulb dimensions

- Height: 110 mm
- Width: 60 mm

Other characteristics

- Mercury content: 0 mg
- Power factor: 0.5
- · Lamp current: 55 mA
- · Lamp Classification Risk Group: RG1

Rated values

- · Rated power: 5.5 W
- Rated luminous flux: 470 lumen
- Rated lifetime: 15000 hour(s)
- Rated beam angle: 200 degree



Issue date 2018-11-21

© 2018 Philips Lighting Holding B.V. All Rights reserved.

Version: 6.1.1

Specifications are subject to change without notice. Trademarks are the property of Philips Lighting Holding B.V. or their respective owners.

12 NC: 9290 012 34201 www.philips.com

* Designed for the comfort of your eyes. Visit www.philips.com/ eyecomfort for flicker, strobe and other criteria and product details. * PstLM is smaller or equal to 1.0 measured according to IEC 61547-1 and IEC 61000-4-15.